



Radna temperatura: -20 °C/+60 °C

Materijali

1	Kučište	Čelik – St 52-3
2	Kugla	Nehrđajući čelik – X 5 Cr Ni 18 10
3	Vreteno	Nehrđajući čelik – X 20 Cr 13
4	Brtva	PTFE
5	O-Ring	Viton
6	Ručka	Čelik – St 37-2

KPF-G DN ... AN150 DP VX PX

ANSI Class 150

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	Težina (kg)
A956023	25	127	110	90	25	180	14,5	79,5	16	4	6,00
A956025	40	165	130	120	40	360	17,5	98,5	16	4	12,00
A956026	50	178	150	130	50	360	19,5	120,5	20	4	17,50
A956028	80	203	190	150	78	460	24,0	152,5	20	4	28,50
A956029	100	229	230	165	99	460	24,0	190,5	20	8	46,50
A956034	150	394	280	–	149	–	25,5	241,5	22	8	161,50

KPF-G DN ... AN300 DP VX PX

ANSI Class 300

Kat. Broj	DN	A	ØB	C	ØD	G	b	ØDk	Ød	Broj rupa	Težina (kg)
A956063	25	165	125	90	25	180	17,5	89,0	20	4	7,50
A956065	40	191	155	120	40	360	21,0	114,5	22	4	15,00
A956066	50	216	165	130	50	360	22,5	127,0	20	8	21,00
A956068	80	283	210	150	78	460	29,0	168,5	22	8	40,50
A956069	100	305	255	165	99	460	32,0	200,0	22	8	64,00
A956071	150	403	320	–	149	–	37,0	270,0	22	12	225,00

Napomena

DN150 s ručnim pužnim pogonom.
Antistatički dizajn i požarna brtva.